

AirOxPro PROGRAMMING MANUAL

For 10" x 54" Systems

- From the time of day screen, press and hold the "Next" and "Down" buttons until the display changes.
- 2. Push the up arrow until you get to "Iron Filter" and hit "Next."
- 3. Set the First Backwash to 10 minutes and hit "Next."
- 4. Set Rinse for 8 minutes... "Next"
- 5. Set the Brine Draw to 40 minutes and hit "Next."......
- 6. Set the Second Backwash to "Off" and hit "Next.".....
- 7. Set the Pounds of Salt to "Off" and hit "Next."
- 8. If metered valve set the Capacity to "5.0x1000" and hit "Next."
- 9. Set the Regen to "Off" and hit "Next."
- 10. Set the Relay to "Off" and hit "Next."
- 11. The Call setting can either be ignored or set to your preference. This setting will display "CALL" on the valve after a time period of your choosing to prompt the user to call for service. Hit "Next" once you've got this set to your preference.
- 12. You should be at the time of day screen again. Press and hold the "Next" and "Up" buttons until the display changes.
- 13. Set the Day Override to "3 Days" and hit "Next."
- 14. Set the Time of Regen to "12:30 AM" and hit "Next."
- 15. Set the Time of Day and the system is ready.